




Aruba Max

Aruba Max with its microperforated, finely sanded surface, offers improved levels of sound absorption and sound attenuation, making it a great choice for classrooms and other areas requiring Class C sound absorption.

Key Features

- Improved aesthetics with discreet perforations, a smoother finish and a class-leading, fully painted whiteness
- Balanced acoustical absorption performance of 0.65 α_w and sound attenuation of 35dB
- Fully painted, reinforced edges for a more robust tile and greater durability
- Easy to handle and re-engineered for a better, easier fit
- Ideal for classroom and general teaching conditions



Edge Detail	Board	Tegular24	Tegular15
Thickness (mm)	18	18	18
Modules (mm)	600 x 600 5471M 1200 x 600 5472M	600 x 600 5473M	600 x 600 5475M
Suspension Systems	Gridline 24 Butt Cut / Joggled	Gridline 24 Butt Cut / Joggled	Gridline 15 Butt Cut / Joggled Interlude HRC Silhouette
Colour	Global White		

Sustainability



46



A



EN 13964 / E1



Acoustics



EN ISO 354
& EN ISO 11654



EN ISO 10848-2
& EN ISO 717-1



EN ISO 140-3
& EN ISO 717-1

Hz α_p

	α_w	D_{nfw}	R_w	Class	NRC	125	250	500	1000	2000	4000
Board, Tegular24, Tegular15	0.65	35 dB	17 dB	C	0.60	0.35	0.45	0.60	0.65	0.70	0.65

Fire Reaction



A2-s1, d0
EN 13501-1

Performances & Features



85%



95% RH



4.3 Kg/m²



If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 134.4.05.24