




## Ceramaguard (100% RH)


With its unique high density mineral composition, Ceramaguard is steam resistant and will retain its physical integrity even when subjected to 100% RH. It also features a washable finish and is lightly fissured to provide acoustic performance.

## Key Features

- 100% RH resistance
- Durable, washable and scrubbable
- Resistant to growth of mould, mildew and bacteria
- Good balance between sound attenuation and absorption
- Ideal for swimming pools, locker rooms, shower areas and indoor parking areas



## Edge Detail Board



<b>Thickness (mm)</b>	15
<b>Modules (mm)</b>	600 x 600 ..... 607M
<b>Suspension Systems</b>	Gridline 24 Butt Cut / Jogged Gridline 24 Corrosive Resistant <sup>1</sup> Prelude 24 Clean Room
<b>Colour</b>	Global White

<b>Sustainability</b>	37		A+	EN 13964 / E1
-----------------------	----	--	----	---------------

<b>Acoustics</b>	EN ISO 354 & EN ISO 11654 $\alpha_w$	EN ISO 10848-2 & EN ISO 717-1 $D_{nfw}$	Class	NRC	125	250	500	1000	2000	4000
Board	0.55(MH)	-	D	0.60	0.25	0.30	0.50	0.80	0.85	0.75

<b>Fire Reaction</b>	Euroclass A1 EN 13501-1
----------------------	----------------------------

<b>Performances &amp; Features</b>	79%	7.3Kg/m <sup>2</sup> 20 Kg/m <sup>2</sup> > if wet				
	100% RH					

While this product is suitable for high humidity environments, it is not suitable to be fitted directly over a swimming pool.

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email [enquiries@zentia.com](mailto:enquiries@zentia.com)

TDS 071.2.03.24