




Hydrabloc ($\leq 100\%$ RH)

Hydrabloc can resist permanent RH up to 95% and temporary conditions of up to 100% RH. Install with Gridline 24 Corrosive Resistant grid system for higher humidity areas.

Key Features

- Stable at humidity levels of up to 100% RH
- Can be installed in temperatures ranging from 0°C to 40°C
- High acoustic absorption up to 1.00 α_w
- Ideal for WC, shower areas and hydrotherapy rooms. Should be installed on Corrosive Resistant grid



Edge Detail	Board	Tegular24
Thickness (mm)	15	15
Modules (mm)	600 x 600 3687M 1200 x 600 3688M	600 x 600 3689M
Suspension Systems	Gridline 24 Joggled/Butt Cut Gridline 24 Corrosive Resistant Prelude 24 Sixty ² Cleanroom 24 Butt Cut	Gridline 24 Joggled/Butt Cut Gridline 24 Corrosive Resistant Prelude 24 Sixty ² Cleanroom 24 Butt Cut

Colour Global White

Sustainability



85



EN 13964 / E1

Acoustics



EN ISO 354
& EN ISO 11654



EN ISO 10848-2
& EN ISO 717-1

	Hz α_p									
	α_w	D_{nfw}	Class	NRC	125	250	500	1000	2000	4000
Board	1.00	-	A	0.95	0.55	0.85	1.00	0.90	1.00	1.00

Fire Reaction



A2-s1,d0
EN 13501-1

Performances & Features



89%



≤100%
RH



30 Year
System
Guarantee



2 Kg/m² Board
2.5 Kg/m² Tegular24



BIM
READY

While this product is suitable for high humidity environments, it is not suitable to be fitted directly over a swimming pool.

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 181.3.06.24