

Key Features

- // Up to 99% RH
- Available in Board edge
- Offers Class C sound absorption and good attenuation for excellent acoustic performance
- Available in Global White, giving warm and damp spaces a brighter and cooler appearance
- Ideal for high humidity areas such as changing rooms
- Excellent technical performance in humid conditions when used alongside Gridline 24 Corrosive Resistant suspended ceiling grid



Edge Detail	Board										
Thickness (mm)				15							
Modules (mm)	600 x 600 5499M										
Suspension Systems	Gridline 24 Butt Cut / Joggled Gridline 24 Corrisive Resistant Prelude 24 Sixty²										
Colour	Global White										
Sustainability								OOK AN	rofins		
	44		Α		EN 139	64 / E1		IFIED	PROD		
Acoustics		ENISO 354 &ENISO 11654	EN ISO 10848-2 & EN ISO 717-1								
		a	D	Class	NRC	125	250		α _P	2000	4000
	 Board	0.60	D _{nfw} 34 dB	Class	0.55	0.35	0.45	0.60	0.60	0.60	4000 0.60
Fire Reaction											
riie Reaction	Euroclass A2 EN 13501-1	?-s1, d0									

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on 0800 371 849 or email enquiries@zentia.com

3.6 Kg/m²

99% RH



30 Year

System

READY



Performances

& Features

Lifetime